

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 1364.1001-CIP2/RAG

First Named Inventor or Application Identifier:

Steven D. SCHERF

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: **Assistant Commissioner for Patents**
Box Patent Application
Washington, DC 20231

1. ☒ Fee Transmittal Form
2. ☒ Specification, Claims & Abstract [Total Pages: 27]
3. ☒ Drawing(s) (35 USC 113) [Total Sheets: 4]
4. ☒ Oath or Declaration [Total Pages: 1]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed)
 - i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation by Reference (usable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☐ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application, status still proper and desired.
15. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☐ Other:

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☒ Continuation-in-part (CIP) of prior application No: 09/354,164

18. CORRESPONDENCE ADDRESS

STAAS & HALSEY LLP
Attn: Richard A. Gollhofer
700 Eleventh Street, N.W., Suite 500
Washington, DC 20001

Telephone: (202) 434-1500
Facsimile: (202) 434-1501

METHOD AND SYSTEM FOR FINDING MATCH IN DATABASE RELATED TO WAVEFORMS

CROSS-REFERENCE TO RELATED APPLICATIONS

This is a continuation-in-part of co-pending U.S. Patent Application Serial No.

5 09/354,164 filed July 16, 1999, which is a divisional of U.S. Patent Application Serial No.
08/838,082, incorporated herein by reference, which issued November 16, 1999 as U.S.
Patent No. 5,987,525.

BACKGROUND OF THE INVENTION

Field of the Invention

10 The present invention is directed to locating records in a database and, more
particularly, to locating a match for a waveform in a database of records representing
waveforms.

Description of the Related Art

15 Over the past few years, on-line services have experienced explosive growth and have
become a major new form of entertainment. Alongside this new entertainment, more
traditional forms such as musical recordings have continued to be consumed on a massive
scale.

20 The traditional experience of the musical recording is listening by a small group of
persons gathered together in a room. The music fills the room acoustically, but there is little
associated visual content, and there is only a limited interaction with the recording, consisting
essentially of deciding which tracks to play and performing simple transformations on the
recorded sound, such as setting the volume or applying an audio equalizer. This traditional
experience dates back to the early age of 78 r.p.m. musical recordings almost a century ago.

The traditional production of a musical recording complements the traditional experience of the recording. The recording is produced in a number of recording sessions, subject to careful mixing and editing, and then released to the public. At that point, the recording is in a fixed form, nowadays an audio CD, whose purpose is to record as faithfully as possible the final sonic experience designed by its authors, the musicians, producer, and recording engineers.

Music videos have supplemented the traditional experience of musical recordings by allowing the association of visual content with tracks of such a recording. In practice, however, music videos have been broadcast, with all the problems of lack of user control which that implies, and they have not contributed to interactivity or participation by the consumer.

On-line services offer opportunities for enriching the experience associated with musical recordings. The present invention is addressed to computer programs, systems, and protocols which can fulfil this promise.

SUMMARY OF THE INVENTION

It is therefore an object of this invention to provide computer programs, systems, and protocols which allow producers to deliver entertainment complementary to musical recordings by means of on-line services such as the Internet. It is a further object of this invention to provide computer programs, systems, and protocols which allow such complementary entertainment to be meaningfully interactive for the consumer, such that the consumer can also be a creator of the experience.

It is a further object of the invention to achieve the foregoing objects by means of implementations designed to attain integration with existing environments and programs, particularly on the Internet, while retaining the flexibility to adapt to the continuing evolution of standards for on-line services.

In one aspect of the invention, software is provided which permits a computer program running on a remote host to control a compact disc (CD) player, DVD player, or the like on a user's computer. (For convenience, we use the term "CD player" to refer also to DVD players and similar devices.) The software is designed to permit the remote host both to initiate actions on the CD player and to become aware of actions which the user has initiated by other control means, such as the buttons on the CD player's front panel or a different CD player control program. This aspect of the invention is a building-block for the provision of complementary entertainment for musical recordings when those recordings are fixed in the prevailing contemporary form, the audio CD.

In a second aspect of the invention, visual content, including interactive content, may be delivered over an on-line service in such a way that it is synchronized to the delivery of content from a musical recording. Such visual content may, for example, be synchronized to the playing of an audio CD in the user's computer. The visual content is thematically linked to the musical recording, for example in the manner of a music video.

In a third aspect of the invention, a method is provided for assigning a unique identifier to musical recordings consisting of a number of tracks. A unique identifier is a useful complement to the delivery of visual content in conjunction with the playing of an audio CD in that it allows the software which delivers the visual content to be sure that the audio CD is in fact the correct CD to which the visual content corresponds. If the visual content is designed, for example, to accompany the Rosary Sonatas of Heinrich Ignaz Franz Biber, it would presumably not function well if the CD in the user's player were the soundtrack for the film Mary Poppins. The unique identifier also allows a CD to be used as a key to access a premium Web area. Furthermore, the unique identifier can allow the user to be directed to an area of the Web corresponding to the CD which is in the user's machine.

In a fourth aspect of the invention, the immensely popular on-line service generally referred to as a "chat room" may be enhanced by means of a link to a musical recording to which all persons in the room are listening. The chat room experience as it exists today in on-

line services has a disembodied quality by comparison with traditional face-to-face social encounters, in which there are identifiable surroundings. The only common experience to the chat users today are the words of the chat as they fly by on a computer screen, and perhaps the user icons ("avatars") or other visual content occupying a small space on the screen. The use of a musical recording in conjunction with a chat room opens up the possibility of restoring to the experience a degree of the shared ambience of traditional social encounters. Furthermore, the musical recording offers a focal point that allows chat-seekers to group together by means of shared interests in a particular type of recording.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of the environment in which the preferred embodiment operates.

FIG. 2 is a flowchart of the synchronization code of the invention.

FIG. 3 is a flowchart of the sequence of operations for connection to a chat room focused on a musical recording.

FIGS. 4A and 4B are explanatory diagrams of waveform analysis according to the present invention.

DESCRIPTION OF PREFERRED EMBODIMENTS

The preferred embodiment of this invention operates on the World Wide Web. The software implementation environment provided by the World Wide Web is described in a number of books, for example, John December & Mark Ginsburg, HTML 3.2 and CGI Unleashed (1996). The World Wide Web is based on a network protocol called HTTP (hypertext transfer protocol), which is described in T. Berners-Lee et al., Hypertext Transfer Protocol--HTTP/1.0 (Internet Request for Comments No. 1945, 1996). The HTTP protocol

must be run atop a general connection-oriented protocol, which today is generally TCP/IP, described in Douglas E. Comer, *Internetworking with TCP/IP* (3d ed. 1995). However, the invention described here is not limited to HTTP running over any particular kind of network software or hardware. The principles of the invention apply to other protocols for access to remote information that may come to compete with or supplant HTTP.

As shown in FIG. 1, a Web user sits at his or her computer and runs a computer program called a browser. The browser sends out HTTP requests to other computers, referred to as servers. In requests, particular items of data, referred to as resources, which are available on servers, are referred to by means of uniform resource locators (URL's), character strings in a particular format defined in Berners-Lee et al., *supra*. A URL includes both an identification of the server and an identification of a particular item of data within the server. Reacting to the requests, the servers return responses to the user's browser, and the browser acts upon those responses, generally by displaying some sort of content to the user.

The content portion of the responses can be a "Web page," expressed in the hypertext markup language (HTML). That language allows one to express content consisting of text interspersed with bitmap-format images and links (also known as anchors and hyperlinks). The links are further URL's to which the browser may, at the user's prompting, send further requests.

The responses can also include more complex commands to be interpreted by the browser, e.g., commands which result in an animation. HTML itself does not define complex commands, but rather they are considered to belong to separately-defined scripting languages, of which the two most common ones are JavaScript and VBScript.

In addition to extending the function of the browser by means of code written in a scripting language, it is also possible to extend the function of a browser with compiled code. Such compiled code is referred to as a "plug-in." The precise protocol for writing a plug-in is dependent on the particular browser. Plug-ins for the Microsoft browser are referred to by the name of ActiveX controls.

Plug-ins may be very complex. A plug-in which may advantageously be used in connection with the invention is Shockwave from Macromedia. It permits animations which are part of a server response to be downloaded and played to the user. Shockwave defines its own scripting language called Lingo. Lingo scripts are contained within the downloadable
 5 animations which the Shockwave plug-in can play. The general format of a Shockwave animation is a timeline consisting of a series of frames, together with a number of visual objects which appear, perform motions, and disappear at particular frames within the timeline. To achieve more complex effects within a Shockwave animation, Lingo scripts may be invoked in addition to predefined visual objects.

10 A preferred embodiment of the invention employs a plug-in, referred to as the command plug-in, which provides to a scripting language the ability to command in a detailed fashion the playing of a musical recording. The command plug-in should provide, at a minimum, the following basic functions:

(1) Start and stop play.

15 (2) Get current track and position within the track.

(3) Seek to a track and a position within the track.

(4) Get and set volume.

(5) Get information regarding the CD (e.g., the number of tracks, their lengths, the pauses between tracks).

20 (6) Get information regarding the capabilities of the CD drive.

Other functions may be provided, limited only by what the underlying operating system services are able to provide.

The command plug-in is preferably written in a conventional programming language such as C++. The plug-in must conform to the existing standards for plug-ins, such as those required of Microsoft ActiveX objects. In order to obtain the information and carry out the functions which the command plug-in makes available to the scripting language, the command plug-in relies on functions which provide control and information regarding the playing musical recording. These functions will depend on the precise source of the recording. If, as in the currently preferred embodiment, the recording is being played on an audio CD in the computer CD player, and if the browser is running under Microsoft Windows 3.1 or Windows 95, these functions would be the MCI functions, which form a part of the Win32 application programming interface. These functions are documented, for example, in Microsoft Win32 Programmer's Reference. Different functions may be provided by streaming audio receivers, as for example receivers which capture audio which is coming into the user's computer over a network connection in a suitable audio encoding format such as MPEG.

An important point to note about the implementation of the command plug-in is that the operations which it carries out, as for example seeks, may take times on the order of a second. It is undesirable for the command-plug in to retain control of the machine during that interval, so it is important that the plug-in relinquish control of the machine to the browser whenever a lengthy operation is undertaken, and report on the results of the operation via the asynchronous event handling capability used in the common scripting languages.

Given the above summary of the functions which the command plug-in provides, a general knowledge of how to write plug-ins (e.g., of how to write ActiveX objects), and a knowledge of the relevant application programming interface for controlling the play of the musical recording (e.g., MCI in Win32), a person skilled in the art could readily and without undue experimentation develop an actual working command plug-in. For this reason, further details of how the command plug-in is implemented are not provided here.

The existence of a command plug-in providing the functions listed above to a scripting language is a foundation on which entertainment complementary to a musical recording may be constructed. In particular, it is possible to devise, building on this foundation, a method for synchronizing the display of visual content by means of the scripting language with the events
 5 which are occurring on the audio CD.

In a preferred embodiment of the invention, the synchronization of the visual content to the audio CD proceeds as follows. The visual content is provided by means of a Shockwave animation, which is downloaded from the server and displayed for the user by means of a Shockwave plug-in. This downloading may take place before the animation is displayed, or
 10 alternatively it may take place as the animation is being displayed, provided the user's connection to the network is fast enough to support download at an appropriate speed. The downloading is a function provided by the Shockwave plug-in itself.

As the Shockwave animation is played, a Lingo script executes each time a frame finishes displaying. The Lingo script contains a description of the relationship which should
 15 exist between frames of the animation and segments of the musical recording, identified by track number and by time. The Lingo script determines, by means of the command plug-in described above, at which track and time the play of the audio CD is. It then refers to the description in order to determine which frames of the animation correspond to that portion of the audio CD. If the current frame is not one of those frames, the Lingo script resets the time
 20 line of the animation so that the animation will begin to play at the frame which corresponds to the current position of the audio CD. This permits the visual content to catch up if it ever lags the CD, for example because downloading from the network has fallen behind, because the user's computer lacks the cycles to play the animation at full speed, or because the user has fast forwarded the CD.

25 In a variant form of this synchronization algorithm (shown in FIG. 2), the frames of the animation are arranged into groups of contiguous frames. A correspondence is established between each such group of frames and a particular segment of the audio recording (box 200 in

FIG. 2). At the end of each frame of the animation, the audio play position is determined (box 210). A test is done to determine whether the audio play position is within the segment of the recording that corresponds to the group of frames to which the next sequential frame belongs (box 215). If the audio play position is within that segment, the playback of the animation
 5 proceeds with that next frame (box 230). If the audio play position is not within that segment, then the playback of the animation is advanced to the frame corresponding to where the audio is (boxes 220 and 225).

A further aspect of the invention is the ability, by making use of the command plug-in, to provide a technique for establishing a unique identifier for a recording which may be stored
 10 in mass storage, whether integrated circuit, magnetic (e.g., hard disk), or any other medium, or on a removable medium, such as an audio CD, or integrated circuit memory, such as compact flash memory, Memory Stick™, etc., accessed by a CD-ROM drive of a computer, MP3 player/recorder or any other device capable of accessing the medium. The unique identifier may be based on the number and lengths of the tracks (measured in frames, i.e.,
 15 1/75ths of a second) from Table of Contents (TOC) data or the content of the recording itself. The identifier could simply be a concatenation of the track lengths that can be used with a fuzzy comparison algorithm and also for more precise matching if more than one possible match is located.

Following is an example of a fuzzy comparison algorithm that can be used with the
 20 present invention. For each of the two audio CDs to be compared, one determines the lengths of all the tracks in the recordings in milliseconds. One then shifts each of the track lengths to the right by eight bits, in effect performing a truncating division by $2^8 = 256$. One then goes through both of the recordings track by track, accumulating two numbers as one proceeds, the match total and the match error. These numbers are both initialized to zero at the start of the
 25 comparison. For each of the tracks, one increments the match total by the shifted length of that track in the first CD to be compared, and one increments the match error by the absolute value of the difference between the shifted lengths of the track in the two CDs. If one of the

CDs has fewer tracks than the other, when one gets to the last track in the CD with fewer tracks, one continues with the tracks in the other CD, incrementing both the match total and the match error by the shifted lengths of the remaining tracks. Following these steps of going through the tracks, the algorithm then divides the match error by the match number, subtracts the resulting quotient from 1, and converts the difference to a percentage which is indicative of how well the two CDs match.

Use of track length to create an identifier for a recording is best suited to media that have multiple tracks and preferably those that store such information in a table of contents or TOC, such as CDs and DVDs. Furthermore, use of track length or TOC data has been found to work best with fuzzy matching, but this sometimes results in finding more than one possible match. An alternative or supplement for TOC data is to use the content of the recording. However, it is desirable to use a content-based identifier that is relatively small, to minimize storage space and bandwidth requirements.

An embodiment of the present invention uses an amplitude signature providing a content-based identifier generated from short, e.g., five second sample segments from multiple locations in each track (if there is more than one track in a recording), such as the beginning, middle and end. An example of one such sample segment (the term sample segment is used to distinguish the segments used for generating the identifier from identified segments, i.e., segments identified in the TOC, that are commonly referred to as "tracks" on a CD) is illustrated in Fig. 4A with a waveform 410. According to the present invention, a plurality of amplitude bands or slots are defined and the number of occurrences of all segments of the waveform within each slot are counted. Redbook CD Audio is a sampled digital audio file of 44.1 K samples per channel, 16-bit stereo with 75 frames of data per second. Thus, there are a maximum of 220,500 occurrences in one five second sample segment ($75 \text{ frames/sec} * 588 \text{ samples/frame} * 5 \text{ sec} = 220,500 \text{ samples in 5 seconds of data}$). To ensure uniqueness, it is desirable to use about 2000 (e.g., 2^{11} or 2048) slots, but other sizes, number and types of samples and number of slots can be used, depending on the characteristics of the waveforms

being compared. To simplify the explanation of the invention, a coarser example will be given with respect to Figs. 4A and 4B.

In the preferred embodiment, the first step is to normalize the waveform, so that the first and last slots have at least one occurrence of the waveform. The waveform 410 in Fig. 4A is normalized over the seven slots 420 illustrated in Fig. 4A to produce waveform 410b in Fig. 4B with the slots 420 separately indicated as slots 421-427. In the simplified example provided in Fig. 4B, 16 time samples are taken, one at each of the vertical lines. Thus, there is one sample of waveform 410b in slot 421, three in slot 422, two in slot 423, one in slot 424, two in slot 425, three in slot 426 and four in slot 427. This can be represented by the linear array A1 [1, 3, 2, 1, 2, 3, 4].

If the array A1 is an identifying signature array representing a selected recording for which a match in a database is sought, a fuzzy match may be accomplished by calculating an average of the difference between the elements of A1 and the elements of existing signature arrays. For example, one of the records in the database may have a signature array of A2 [2, 3, 4, 1, 1, 3, 3] for a difference array of [1, 0, 2, 0, 1, 0, 1] or an average difference of 5/7 or 0.714. A "fuzzy match" based on average difference allows for errors in the waveform and imperfect starting locations for the signature generation. However, the average difference that is accepted as a match should be set to minimize false positives. Alternatively, the number or length of the sample segments could be increased to reduce false positives, but this increases the time spent reading the recording and calculating the signature array. For the waveforms that have been tested, an average difference of 10 has been found able to find virtually all possible matches while eliminating a significant number of false positives when using CD waveforms and three sample segments of five seconds each with 2048 slots. Under these conditions it has been found that 256 slots produces too many matches of nonsimilar waveforms and 4000 slots leaves the slots so sparsely populated that there are a large number of near matches. The precise number of slots can be varied depending on the size of the sample segment(s) and the type of waveforms being sampled.

If more than one possible match has been found, more precise comparison of the identifying and existing signature arrays may be performed. The number of slots that match exactly or are within one occurrence of matching may be used. In the example given above, 6 out of 7 or 86% of the elements of arrays A1 and A2 match if an error of one (or one grace) is permitted and 3 out of 7 or 43% of the elements match precisely. It has been found that a better than 80% match for a one grace or a better than 70% match with no grace is likely to be an acceptable match. The grace value can be increased to more than one to allow more forgiveness in matching the waveforms.

A unique identifier for a musical recording may be employed as a database key. A site may maintain a database of information about CDs, for example information about all CDs issued by the particular record company can be maintained on that record company's site. There are various alternative ways for users to navigate this information. For example, they could use a Web page containing many hyperlinks as a table of contents, or they could use a conventional search engine. A third way of searching which is enabled by the unique identifier of the invention is for there to be Web page which invites the user to place in the computer's CD drive the CD about which he or she is seeking information. Upon detection of the presence of the CD in the drive, a script in the Web page computes the unique identifier corresponding to the CD and sends it to the server. The server then displays information about the CD retrieved from a database on the basis of that unique identifier. This information may include a Web address (URL) that is related to the audio CD (e.g., that of the artists' home page), simple data such as the names of the songs, and also complementary entertainment, including potentially photographs (e.g., of the band), artwork, animations, and video clips. It is also possible to arrange things so that, when the user inserts an audio CD into the computer, (i) the Web browser is launched if not already running, (ii) the browser computes the CD's unique identifier and from that unique identifier derives a URL, and (iii) the browser does an HTTP get transaction on that URL.

An alternative application of unique identifiers for musical recordings is to employ an audio CD as a key for entering into a premium area of the Web. There are presently premium areas of the Web to which people are admitted by subscription. A simple form of admission based on the unique identifier is to require, before accessing a particular area of the Web, that the user place in his or her CD drive a particular CD, or a CD published by a particular company or containing the music of a particular band or artist. This is readily accomplished by means of a script which invokes the functions provided by the command plug-in and computes a unique identifier.

A third aspect of the invention is the connection of chat rooms with musical recordings. The goal is to provide all participants in a chat room with the same music at approximately the same time.

The prevailing network protocol for chat services is Internet Relay Chat (IRC), described J. Oikarinen & D. Reed, Internet Relay Chat Protocol (Internet Request for Comments No. 1459, 1993). In this protocol, when one becomes a client of a chat server, one sends the name of a chat room. The chat server receives messages from all of its clients and relays the messages sent in by one client to all the other clients connected in the same room as that client. The messages which a client sends are typically typed in by the user who is running the client, and the messages which a client receives are typically displayed for the user who is running the client to read.

In a preferred embodiment of the invention, a chat client is customized by means of a plug-in, which we will call the chat plug-in. The chat client is started up by a browser as follows (see FIG. 3). The user connects by means of the browser to a central Web page (box 300) which, upon being downloaded, asks that the user insert a CD into his or her player (box 305). A unique identifier of the CD is computed and communicated back to the server by using the control plug-in described above under the command of a script in the central Web page (box 310). The server then employs the unique identifier to determine whether it has a chat room focused on the CD (box 315). This step may be carried out by looking the unique

identifier up in a database using techniques well known in the art. There exists a vast literature on connecting Web pages to databases, e.g., December & Ginsburg, *supra*, chapter 21. If a chat room focused on the CD exists or can be created, the server responds with the name of that chat room, and the browser starts up a chat client on the user's computer as a client of that chat room (box 320).

The chat room's name is set by the server to contain information about the track which the CD is playing in the other chat room clients' machines and the time at which the track started to play, as well as about the volume at which the CD is playing. The chat client plug-in employs that information to direct the control plug-in to set the CD in the user's computer to play in such a manner that it is approximately synchronized to the CD which is playing in the other chat room clients' machines (box 320).

Each user in the chat room is able to control the CD which is playing in his or her machine. Control actions result in the chat plug-in sending messages to the chat server which describe the control action being taken (box 325). For example, such messages may indicate a change in the position of the CD, a change in the volume, or the ejection of the CD to replace it with another. The chat plug-ins running on the other users' machines, upon seeing a message of this kind, replicate the action (as far as possible) on the other users' machines by using the control plug-in described above (box 330).

In a further aspect of the invention, a chat room focused on a particular musical recording might allow for a voting procedure to select particular tracks. A simple voting procedure would be for each chat plug-in to act upon a change message of the kind described in the preceding paragraph only when it sees two identical consecutive change messages. This would mean that in order to change the track which is being played, it would be necessary for two users to change to that track. The number two may be replaced by a higher number.

In a further aspect of the invention the messages delivered to the users of a chat can be driven from a text file rather than manual typing. This would allow a pre-recorded experience

to be played back for a group of chat users. Such a technique may be used to create a pre-recorded, narrated tour of an audio CD.

An important advantage of the preferred embodiment as described above is that it may be used with any chat server software which supports the minimal functionality required by Internet Relay Chat or by a protocol providing similar minimum chat service. The additional software required is located in the chat client plug-in and in the central Web page, with its connection to a database of CD information.

The many features and advantages of the present invention are apparent from the detailed specification and thus, it is intended by the appended claims to cover all such features and advantages of the system which fall within the true spirit and scope of the invention.

Further, numerous modifications and changes will readily occur to those skilled in the art from the disclosure of this invention. It is not desired to limit the invention to the exact construction and operation illustrated and described; accordingly, suitable modification and equivalents may be resorted to, as falling within the scope and spirit of the invention.

CLAIMS

What is claimed is:

1. A method of searching for a match in a database of a plurality of records, where the records in the database correspond to recordings containing waveforms, comprising:

generating an amplitude signature for at least one segment of a selected recording; and

5 determining at least one matching record in the database for the selected recording based on the amplitude signature.

2. A method as recited in claim 1,

further comprising calculating approximate length information for the records in the database and for the selected recording, and

wherein said determining is also based on the approximate length information.

3. A method as recited in claim 2, wherein the recordings have at least one track

wherein said calculating calculates a length of each track of each recording represented in the database and for the selecting recording, and

wherein said determining is also based on the number and length of tracks of the recordings represented in the database and the selected recording.

4. A method as recited in claim 3, wherein the waveforms are represented by sampled digital data in the recordings and the selected recording,

wherein said method further comprises storing an existing signature array for each of the recordings represented in the database, where each element of the existing

5 signature array corresponds to a number of occurrences of the sampled digital data within an amplitude band in at least one segment of the recordings represented in the database, and

wherein said generating produces an identifying signature array with each element of the identifying signature array corresponding to a number of occurrences of the sampled digital data within an amplitude band in the at least one segment of the selected recording.

5. A method as recited in claim 4, wherein said determining includes calculating an average difference between the elements of the identifying signature array and the existing signature array for the recordings represented in the database; and

identifying as a possible match any recording represented in the database for which the average difference is greater than a predetermined value.

6. A method as recited in claim 4, wherein said determining includes calculating a matching percentage of corresponding elements in the identifying signature array and the existing signature arrays within a predetermined number of each other; and

indicating as a possible match any recording represented in the database for which the matching percentage is greater than a predetermined percentage.

7. A method as recited in claim 6, wherein the predetermined number is zero and the predetermined percentage is approximately 70%.

8. A method as recited in claim 6, wherein the predetermined number is one and the predetermined percentage is approximately 80%.

9. A method as recited in claim 4, wherein the recordings are stored on removable storage media possessed by the user.

10. A method as recited in claim 4, wherein the recordings are digital files stored on mass storage accessible by a listener of the selected recording.

11. A method as recited in claim 3, further comprising receiving a query to search for a match between the selected recording and the records in the database, the query including the number of tracks and the length information for the selected recording.

12. A method as recited in claim 1, wherein the waveforms are represented by sampled digital data in the recordings and the selected recording,

wherein said method further comprises storing an existing signature array for each of the recordings represented in the database, where each element of the existing signature array corresponds to a number of occurrences of the sampled digital data within an amplitude band in at least one segment of the recordings represented in the database, and

wherein said generating produces an identifying signature array with each element of the identifying signature array corresponding to a number of occurrences of the sampled digital data within an amplitude band in the at least one segment of the selected recording.

13. A method as recited in claim 12, wherein said determining includes calculating an average difference between the elements of the identifying signature array and the existing signature array for the recordings represented in the database; and

identifying as a possible match any recording represented in the database for which the average difference is greater than a predetermined value.

14. A method as recited in claim 13, wherein said determining includes

calculating a matching percentage of corresponding elements in the identifying signature array and the existing signature arrays within a predetermined number of each other;

10 and

indicating as a possible match any recording represented in the database for which the matching percentage is greater than a predetermined percentage.

15. A method as recited in claim 14, wherein the predetermined number is zero and the predetermined percentage is approximately 70%.

16. A method as recited in claim 14, wherein the predetermined number is one and the predetermined percentage is approximately 80%.

17. A method as recited in claim 12, wherein the recordings are stored on removable storage media possessed by the user.

18. A method as recited in claim 17, wherein the recordings are digital files stored on mass storage accessible by a listener of the selected recording.

19. A method as recited in claim 11,
wherein the selected recording is played at a first location on equipment
possessed by a user, and

wherein said method further comprises:

5

generating a query by the equipment at the first location; and

sending the query to a server at a second location where the database is stored, to search for at least one matching record.

20. A method as recited in claim 19, further comprising sending from the server to the equipment at the first location additional information stored in the at least one approximately matching record and not included in the selected recording.

21. A database system, comprising:

a storage unit storing a database of records including existing signatures for recordings corresponding to the records; and

5 a processing unit, coupled to said storage unit, programmed to generate an identifying amplitude signature for a selected recording, and to determine at least one matching record in the database for the selected recording by comparing the identifying amplitude signature with the existing amplitude signatures in the database.

22. A database system as recited in claim 21,

wherein said storage unit further stores information indicating length and number of identified segments of the recordings, and

5 wherein said processing unit calculates approximate length information for the selected recording and further determines the at least one matching record in the database based on the approximate length information and a number of identified segments in the selected recording and the recordings corresponding to the records in the database.

23. A database system as recited in claim 21, wherein the recordings contain sampled digital data,

5 wherein said storage unit stores the existing signature array with each element corresponding to a number of occurrences of the sampled digital data within an amplitude band in at least one segment of the recordings represented in the database, and

wherein said processing unit generates the identifying signature array with each element corresponding to a number of occurrences of the sampled digital data within an

amplitude band in at least one segment of the selected recording and determines the at least one matching record by calculating an average difference between the elements of the identifying signature array and the existing signature array for the recordings represented in the database and identifying as a possible match any recording represented in the database for which the average difference is greater than a predetermined value.

24. A database system as recited in claim 21, wherein the recordings contain sampled digital data,

wherein said storage unit stores the existing signature array with each element corresponding to a number of occurrences of the sampled digital data within an amplitude band in at least one segment of the recordings represented in the database, and

wherein said processing unit generates the identifying signature array with each element corresponding to a number of occurrences of the sampled digital data within an amplitude band in at least one segment of the selected recording and determines the at least one matching record by calculating a matching percentage of corresponding elements in the identifying signature array and the existing signature arrays within a predetermined number of each other and indicating as a possible match any recording represented in the database for which the matching percentage is greater than a predetermined percentage.

25. A database system as recited in claim 21, further comprising a communication unit, coupled to said storage unit, to receive a query to search for a match between the selected recording and the records in the database, the query including the number of segments and the length information for the selected recording.

26. A database system as recited in claim 25, wherein the recordings corresponding to the records in the database and the selected recording each contain at least an audio portion and the number of segments are the number of tracks in the audio portion.

27. A database system as recited in claim 26, wherein the recordings are stored on removable storage media possessed by the user.

28. A database system as recited in claim 26, wherein the recordings are digital files stored on mass storage accessible by a listener of the selected recording.

29. A database system as recited in claim 25,
wherein said processing unit, storage unit and communication unit are at a first location, and

wherein said database system further comprises:

equipment possessed by a user at a second location, remote from the first location, to generate the query and play the selected recording; and

a communication network at least temporarily coupling said equipment and said communication unit to send the query from said equipment to said communication unit.

30. A database system as recited in claim 29, wherein said communication unit sends to the equipment via said communication network additional information stored in the at least one approximately matching record and not included in the selected recording.

31. At least one computer program stored on a computer-readable medium, embodying a method of searching for a match in a database of a plurality of records, where the records in the database correspond to recordings containing waveforms, comprising:

5 generating an amplitude signature for at least one segment of a selected recording; and
determining at least one matching record in the database for the selected recording based on the amplitude signature.

32. At least one computer program as recited in claim 31,
further comprising calculating approximate length information for the records in
the database and for the selected recording, and
wherein said determining is also based on the approximate length information.

33. At least one computer program as recited in claim 32, wherein the recordings have
at least one track

wherein said calculating calculates a length of each track of each recording
represented in the database and for the selecting recording, and

5 wherein said determining is also based on the number and length of tracks of the
recordings represented in the database and the selected recording.

34. At least one computer program as recited in claim 33, wherein the waveforms are
represented by sampled digital data in the recordings and the selected recording,

wherein said method further comprises storing an existing signature array for
each of the recordings represented in the database, where each element of the existing
5 signature array corresponds to a number of occurrences of the sampled digital data within an
amplitude band in at least one segment of the recordings represented in the database, and

wherein said generating produces an identifying signature array with each
element of the identifying signature array corresponding to a number of occurrences of the
sampled digital data within an amplitude band in the at least one segment of the selected
10 recording.

35. At least one computer program as recited in claim 34, wherein said determining
includes

calculating an average difference between the elements of the identifying signature array and the existing signature array for the recordings represented in the database;

5 and

identifying as a possible match any recording represented in the database for which the average difference is greater than a predetermined value.

36. At least one computer program as recited in claim 34, wherein said determining includes

calculating a matching percentage of corresponding elements in the identifying signature array and the existing signature arrays within a predetermined number of each other;

5 and

indicating as a possible match any recording represented in the database for which the matching percentage is greater than a predetermined percentage.

37. At least one computer program as recited in claim 34, wherein the recordings are stored on removable storage media possessed by the user.

38. At least one computer program as recited in claim 34, wherein the recordings are digital files stored on mass storage accessible by a listener of the selected recording.

39. At least one computer program as recited in claim 33, further comprising receiving a query to search for a match between the selected recording and the records in the database, the query including the number of tracks and the length information for the selected recording.

40. At least one computer program as recited in claim 31, wherein the waveforms are represented by sampled digital data in the recordings and the selected recording,

wherein said method further comprises storing an existing signature array for each of the recordings represented in the database, where each element of the existing
5 signature array corresponds to a number of occurrences of the sampled digital data within an amplitude band in at least one segment of the recordings represented in the database, and

wherein said generating produces an identifying signature array with each element of the identifying signature array corresponding to a number of occurrences of the sampled digital data within an amplitude band in the at least one segment of the selected
10 recording.

41. At least one computer program as recited in claim 40, wherein said determining includes

calculating an average difference between the elements of the identifying signature array and the existing signature array for the recordings represented in the database;

5 and

identifying as a possible match any recording represented in the database for which the average difference is greater than a predetermined value.

42. At least one computer program as recited in claim 40, wherein said determining includes

calculating a matching percentage of corresponding elements in the identifying signature array and the existing signature arrays within a predetermined number of each other;

5 and

indicating as a possible match any recording represented in the database for which the matching percentage is greater than a predetermined percentage.

43. At least one computer program as recited in claim 40, wherein the recordings are stored on removable storage media possessed by the user.

44. At least one computer program as recited in claim 43, wherein the recordings are digital files stored on mass storage accessible by a listener of the selected recording.

45. At least one computer program as recited in claim 40,
wherein the selected recording is played at a first location on equipment
possessed by a user, and

wherein said method further comprises:

5 generating a query by the equipment at the first location; and
 sending the query to a server at a second location where the database is
stored, to search for at least one matching record.

46. At least one computer program as recited in claim 45, further comprising sending
from the server to the equipment at the first location additional information stored in the at
least one approximately matching record and not included in the selected recording.

METHOD AND SYSTEM FOR FINDING MATCH
IN DATABASE RELATED TO WAVEFORMS

ABSTRACT OF THE DISCLOSURE

To determine whether there is a record in a database corresponding to a file containing

5 a waveform, one or more segments of a digitally sampled waveform are used to form an amplitude signature of the waveform. The amplitude signature is generated by counting the

number of occurrences within the segment(s) of the waveform in each of a plurality of amplitude bands or slots. The amplitude signature of the waveform undergoes a fuzzy

comparison with amplitude signatures in the database. If more than one potential match is

10 found, a more precise comparison is made. This technique can be used with compact discs (CDs) by taking, e.g., five second sample segments from the beginning, middle and end of

each track to detect the amplitude of the waveform in each of 558 samples in the 1/75 second frames recorded in the sample segments of the CD. A CD amplitude signature may be formed

of approximately 2000 amplitude bands or slots from the lowest amplitude to the highest

15 amplitude of the waveform by accumulating the occurrence of signals within each amplitude slot for all of the sample segments of the CD. The amplitude signature can be used to

distinguish between multiple potential matches obtained based on table of contents (TOC) data for the CD indicating the number of tracks and the length of each.




Figure 1




Figure 2




Figure 3




Figure 4A




Figure 4B

COMBINED DECLARATION/POWER OF ATTORNEY FOR UTILITY/DESIGN PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHOD AND SYSTEM FOR FINDING MATCH IN DATABASE RELATED TO WAVEFORMS

the specification of which is attached hereto, unless the following box is checked:

☐ was filed on _____ as United States Application Number or PCT International Application Number _____ and was amended on (if applicable) _____.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56.

I hereby claim foreign priority benefit(s) under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application(s) for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Not Claimed

(Number) (Country) Day/Month/Year Filed

(Number) (Country) Day/Month/Year Filed

I hereby claim the benefit under 35 U.S.C. § 120 or § 119(n) of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application(s) in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

09/354,164	July 16, 1999	Pending
(Application Serial No.)	(Filing Date)	(Status -- patented, pending, abandoned)
06/838,062	April 15, 1997	Patented
(Application Serial No.)	(Filing Date)	(Status -- patented, pending, abandoned)

I hereby appoint the following attorneys and agent to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

James D. Halsey, Jr., 22,729; Harry John Staas, 22,010; David M. Pitcher, 25,908; John C. Garvey, 28,607; J. Randall Beckers, 30,358; William F. Herbert, 31,024; Richard A. Golhofer, 31,106; Mark J. Henry, 36,162; Gene M. Garner II, 34,172; Michael D. Stein, 37,210; Paul I. Kravetz, 35,230; Todd E. Marlette, 35,269; Norman L. Ourada, 41,235; Deborah S. Gladstein, 43,636; Jonathan H. Muskin, 43,824; Stephen Boughner, 45,317; John H. Stowe, 32,863; C. Joan Gilsdorf, 43,635; Mehdi Sheikherz, 41,307; James G. McEwen, 41,983; Michael J. Badagliacca, 39,099; Alicia M. Choi, P-46,621; and William M. Schertler, 35,348 (agent)

Address all correspondence to: STAAS & HALSEY LLP, 700 Eleventh Street, N.W., Suite 500, Washington, D.C. 20001

Direct all telephone calls to: (202) 434-1500 - Facsimile No. (202) 434-1501

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor Steven D. SCHERF

Inventor's Signature STEVEN D. SCHERF Date July 21, 2000

Residence Fremont, California Citizenship U.S.A.

Post Office Address 6040 Mollinari Terrace, Fremont, CA 94555

Full name of second joint inventor, if any Paul E. ALANN

Second Inventor's Signature PAUL E. ALANN Date July 21/00

Residence Kensington, California Citizenship U.S.A.

Post Office Address 41 Ardmore Road, Kensington, CA 94707

☐ Additional inventors are being named on separately numbered sheets attached hereto.